2024 KLX110R L

Starting At Rs.3,12,000/ (Ex-Showroom)

GET ON-ROAD PRICE

TYRE - REAR

WHEELBASE

SEAT HEIGHT

CURB MASS

GROUND CLEARANCE

(https://kawasaki-india.com/on-road-price-estimator/)

*Product pictures shown are for illustration purpose only.

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.



AVAILABLE COLOURS



Lime Green

Engine & Transmission	
ТҮРЕ	4st, 1-cyl, SOHC, 2val, Air-cooled
DISPLACEMENT	112 cm3 /111 cm3 (JPN)
BORE AND STROKE	53.0 x 50.6 mm
COMPRESSION RATIO	9.5
VALVE SYSTEM	-
FUEL SYSTEM	-
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	DC-CDI
STARTING	Electric & Kick
LUBRICATION	Forced Lub. Wet
TRANSMISSION	4-speed, return
MAXIMUM POWER	-
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	-
ELECTRONIC RIDER AID	
Dimensions & Chassis	
FRAME TYPE	Backbone
RAKE / TRAIL	24.2/ 47 mm
TYRE - FRONT	60/100-14M/C (29M) (BRA)

80/100-12M/C (50M) (BRA)

1,075 mm

265 mm

730 mm

76 kg

FUEL CAPACITY	3.6 litres
OVERALL DIMENSIONS (L X W X H)	1560x650x990mm
Brakes & Suspension	
FRONT / WHEEL TRAVEL	Telescopic fork/ 140 mm
REAR / WHEEL TRAVEL	Mono Shock Swingarm/ 132 mm
BRAKE - FRONT	Drum 90 mm
CALIPER - FRONT	-
BRAKE - REAR	Drum 110 mm
CALIPER - REAR	-

Dimensions & Chassis