

2022L KLX450RStarting At **Rs.8,99,000** (Ex-Showroom)**GET ON-ROAD PRICE**[\(https://kawasaki-india.com/on-road-price-estimator/\)](https://kawasaki-india.com/on-road-price-estimator/)

*Product pictures shown are for illustration purpose only.

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.

**AVAILABLE COLOURS**

Lime Green

Engine & Transmission	
TYPE	Liquid-cooled, 4-stroke Single
DISPLACEMENT	449 cm ³
BORE AND STROKE	96.0 x 62.1 mm
COMPRESSION RATIO	12.0:1
VALVE SYSTEM	DOHC, 4 valves
FUEL SYSTEM	Carburetor: Keihin FCR-MX40
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	Digital AC-CDI
STARTING	Electric & Kick
LUBRICATION	Forced lubrication, semi dry sump
TRANSMISSION	5 Speed, Return
MAXIMUM POWER	-
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	-
Dimensions & Chassis	
FRAME TYPE	Perimeter, aluminium
RAKE / TRAIL	28.0° / 122 mm
TYRE - FRONT	80/100-21M/C 51P
TYRE - REAR	120/90-18M/C 65P
WHEELBASE	1,480 mm
GROUND CLEARANCE	315 mm
SEAT HEIGHT	935mm
CURB MASS	126 Kg
FUEL CAPACITY	8 liters
OVERALL DIMENSIONS (L X W X H)	2,175 x 820 x 1,250 mm
Brakes & Suspension	
FRONT / WHEEL TRAVEL	48 mm inverted AOS type telescopic fork with 22-way compression and 18-way rebound damping / 305mm
REAR / WHEEL TRAVEL	Uni-Trak with 22-way low-speed, 2 turns or more high-speed compression damping, 22 way rebound damping and adjustable spring preload / 315mm
BRAKE - FRONT	Single semi-floating ø250 mm petal disc
CALIPER - FRONT	Dual piston
BRAKE - REAR	Single ø240 mm petal disc
CALIPER - REAR	Single piston

