

2024 NINJA 650 BS6

Starting At Rs.7,16,000 (Ex-Showroom)

GET ON-ROAD PRICE[\(https://kawasaki-india.com/on-road-price-estimator/\)](https://kawasaki-india.com/on-road-price-estimator/)

*Product pictures shown are for illustration purpose only.

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.

**AVAILABLE COLOURS****LIME GREEN****Engine & Transmission**

TYPE	Liquid-cooled, 4-stroke Parallel Twin
DISPLACEMENT	649 cc
BORE AND STROKE	83.0 mm x 60.0 mm
COMPRESSION RATIO	10.8:1
VALVE SYSTEM	DOHC, 8 valves
FUEL SYSTEM	Fuel injection: ø36 mm x 2 with dual throttle valves
FUEL TYPE / MINIMUM OCTANE RATING	Unleaded petrol/RON91
IGNITION	Digital
STARTING	Electric
LUBRICATION	Forced lubrication, semi-dry sump
TRANSMISSION	6 Speed, Return
MAXIMUM POWER	50.2 kW {68 PS} / 8,000 rpm
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	64.0 N.m {6.5 kgf.m} / 6,700 rpm
ELECTRONIC RIDER AID	Kawasaki Traction Control (KTTC - 2 Modes)

Dimensions & Chassis

FRAME TYPE	Trellis, high-tensile steel
RAKE / TRAIL	24° / 100 mm
TYRE - FRONT	120/70ZR17M/C (58W)
TYRE - REAR	160/60ZR17M/C (69W)
WHEELBASE	1,410 mm
GROUND CLEARANCE	130 mm
SEAT HEIGHT	790 mm
CURB MASS	196 kg
FUEL CAPACITY	15 litres
OVERALL DIMENSIONS (L X W X H)	2,115 x 740 x 1,145 mm

Brakes & Suspension

FRONT / WHEEL TRAVEL	ø41 mm telescopic fork / 125 mm
----------------------	---------------------------------

Brakes & Suspension

REAR / WHEEL TRAVEL	Horizontal Back-link with adjustable preload / 130 mm
BRAKE - FRONT	Dual semi-floating ø300 mm petal discs
CALIPER - FRONT	Dual piston
BRAKE - REAR	Single ø220 mm petal disc
CALIPER - REAR	Single-piston